

For Global Market



GH SOLAR

Polycrystalline

Black PV Module

GH(250-280)P-60 Series

- ▶ High PID resist performance
- ▶ Reducing cell series resistance
- ▶ Steady power output
- ▶ More power output

System voltage 1000V/1500V standard

250	260	265	270	275	280
-----	-----	-----	-----	-----	-----

EN

ELECTRICAL SPECIFICATIONS								
STC rated output (P _{mpp})*	250 Wp	260 Wp	265 Wp	270 Wp	275 Wp	280 Wp		
PV Module size	1640*992*35 MM							
Standard sorted output	0/+5 Wp							
Warranted power output STC (P _{nominal})	250Wp	260 Wp	265 Wp	270 Wp	275 Wp	280 Wp		
Rated voltage (V _{mpp}) at STC	30.48 V	30.88 V	30.92 V	31.08 V	31.12 V	31.16 V		
Rated current (I _{mpp}) at STC	8.21 A	8.43 A	8.58 A	8.70 A	8.85 A	8.99 A		
Open circuit voltage (V _{oc}) at STC	37.47 V	37.72 V	37.87 V	38.00 V	38.45 V	38.85 V		
Short circuit current (I _{sc}) at STC	8.81A	8.95A	9.18 A	9.45 A	9.52 A	9.67 A		
Module efficiency	15.4%	16.0%	16.3%	16.6%	16.9%	17.2%		
Rated output (P _{mpp}) at NOCT	187.5 Wp	195.0 Wp	198.8 Wp	202.5 Wp	206.3 Wp	210.1 Wp		
Rated voltage (V _{mpp}) at NOCT	27.73 V	27.94 V	27.98 V	28.12 V	28.15 V	28.17 V		
Rated current (I _{mpp}) at NOCT	6.90 A	6.98 A	7.10 A	7.20 A	7.33 A	7.46 A		
Open circuit voltage (V _{oc}) at NOCT	34.24 V	34.46 V	34.60 V	34.71 V	35.13 V	35.16 V		
Short circuit current (I _{sc}) at NOCT	7.45 A	7.54 A	7.73 A	7.96 A	8.02 A	8.09 A		
Temperature coefficient (P _{mpp})			- 0.407%/K		Maximum system voltage (IEC)		1000V _{DC} / 1500V _{DC}	
Temperature coefficient (I _{sc})			+0.049%/K				Number of diodes	
Temperature coefficient (I _{mpp})			- 0.000%/K		Maximum series fuse rating		15 A	
Temperature coefficient (V _{mpp})			- 0.408%/K					
Temperature coefficient (V _{oc})			- 0.310%/K					
Normal operating cell temperature (NOCT)		46±2°C						

* Measurement tolerance +/- 3%




GH Solar

RELATED PARAMETERS	
Cell type	Polycrystalline
Number of cells / cell arrangement	60 / 6 x10
Cells dimension	6"
Packing unit	30 modules
Weight of packing unit (for container)	557 kg / 1228 lbs


MECHANICAL SPECIFICATIONS	
Outer dimensions (L x W x H)	1640 x 992 x 35 mm 64.57 x 39.06 x 1.38 in
Frame technology	Black Aluminum, silver anodized
Module composition	Glass / EVA / Backsheet (black)
Weight (module only)	18 kg / 39.68 lbs
Front glass thickness	3.2 mm / 0.13 in
Junction box IP rating	IP 65/67
① Cable length (IEC)	600/900 mm / 23.62/35.43 in
Cable diameter (IEC)	12 AWG / 4 mm ²
② Maximum load capacity	5400 Pa
Fire performance (IEC)	Class C
Connector type (IEC)	MC4 compatible

Refer to GH Solar crystalline installation manual.

QUALIFICATION AND LINEAR WARRANTIES	
Product standard	IEC61215, 61730
Extended product warranty	12 years
Output decline 3%/year performance P _{mpp} (STC)	1 st year
Output decline 0.7%/year performance P _{mpp} (STC)	2 nd - 25 th years



I-V Curves of PV module MS265P-60 at various solar irradiance



MODULE DIMENSION DETAILS			
Front view	Side view	Rear view	Frame cross section

GH Solar reserves the right of final interpretation.
Specifications and designs included in this datasheet are subject to change without notice.

GH SOLAR
Address: West Xintiandi, Xiacheng Zone, Hangzhou, Zhejiang, PRC.
Website: www.ghsolarpanels.com